



M-TEC  
Livestock Range





## 12FTx6FT TWIN AXLE Standard Features

- Strong aluminium loading gates
- Spare wheel and bracket
- Front fold down flap
- Open side vents
- Plastic mudguards
- 175x75x16 Tyres
- 3.5Tonne coupling
- Parabolic suspension
- Side access doors
- Fully fitted chequered flooring
- LED lighting

## 12FTx6FT TWIN AXLE Optional Extras

- Dividing gate
- Dividing gate hanger
- Effluent tank
- Closed vents
- Top and bottom side vents
- Interior light
- Aluminium mudguards
- M-TEC Safety bar
- Black roof



## 12FTx6FT TRI AXLE Standard Features

- Strong aluminium loading gates
- Spare wheel and bracket
- Front fold down flap
- Open side vents
- Aluminium mudguards
- 175x75x16 Tyres
- 3.5Tonne coupling
- Parabolic suspension
- Side access doors
- Fully fitted chequered flooring
- LED lighting

## 12FTx6FT TRI AXLE Optional Extras

- Dividing gate
- Dividing gate hanger
- Effluent tank
- Closed vents
- Top and bottom side vents
- Interior light
- M-TEC Safety bar
- Black roof



## 14FTx6FT TRI AXLE Features

- Strong aluminium loading gates
- Spare wheel and bracket
- Front fold down flap
- Open side vents
- Aluminium mudguards
- 175x75x16 Tyres
- 3.5Tonne coupling
- Parabolic suspension
- Side access doors
- Fully fitted chequered flooring
- LED lighting

## 14FTx6FT TRI AXLE Optional Extras

- Dividing gate
- Dividing gate hanger
- Effluent tank
- Closed vents
- Top and bottom side vents
- Interior light
- M-TEC Safety bar
- Black roof

## Livestock Features

M-TEC livestock trailers are manufactured for durability and strength, featuring additional elements that set them apart from the competition.

- The chassis layout uses box iron instead of angle iron for increased strength, reducing flex and movement which can cause fatigue in the steel and weaken the structure.
- Spring hangers connected to the box iron ensure stability while turning the trailer with a full livestock load.
- LED lighting is linked via a wiring loom which eliminates junction boxes that are prone to failure in adverse weather.
- Knott running gear, known as the best auto-reverse mechanism in the market, is utilised throughout the M-TEC range.
- Folded aluminium sides provide extra strength at a critical trailer point.
- Sturdy rear posts and robust aluminium loading gates enhance longevity, with integrated LED lighting positioned to avoid damage.
- Slam Shut dividing gates offer adjustable positions for flexibility.
- A black roof option is available across the livestock range, with a unique feature allowing for easy replacement if damaged.
- An effluent tank with removeable lid facilitates thorough cleaning.

*The M-TEC livestock range combines strength, durability and visual appeal in its trailers.*



Model	Imperial Size	Tyres	Unladen Weight	Gross Weight	Internal Length	Internal Width	External Length	External Width	Head Room	Axles
LV_12X62	12FT x 6FT	175x75x16	1160KGS	3500KGS	3615mm	1850mm	4964mm	2311mm	1889mm	2
LV_12X63	12FT x 6FT	175x75x16	1265KGS	3500KGS	3615mm	1850mm	4964mm	2311mm	1889mm	3
LV_14X63	14FT x 6FT	175x75x16	1345KGS	3500KGS	4240mm	1850mm	5500mm	2311mm	1889mm	3

M-TEC award winning livestock trailer is now available with sheep decks. Our unique ramp system provides maximum space with minimum effort. Decks are simply stored when not in use at the front of the trailer.



- 3.5Tonne coupling
- Parabolic suspension
- Side access doors
- Fully fitted chequered flooring
- LED lighting
- 175x75x16 Tyres
- Strong aluminium loading gates
- Interior dividing gate hangers
- Strong aluminium loading gates
- Spare wheel and bracket
- Front fold down flap
- Open side vents
- Plastic mudguards (12FT)
- Aluminium mudguards (14FT)
- Sheep dividing gate

Model	Imperial Size	Tyres	Unladen Weight	Gross Weight	Internal Length	Internal Width	External Length	External Width	Total Head Room	Top Deck Head Room	Bottom Deck Head Room	Axles
LV_12X62SD	12FT x 6FT	175x75x16	1340KGS	3500KGS	3615mm	1850mm	4964mm	2311mm	1889mm	939mm	838mm	2
LV_12X63SD	12FT x 6FT	175x75x16	1145KGS	3500KGS	3615mm	1850mm	4964mm	2311mm	1889mm	939mm	838mm	3
LV_14X63SD	14FT x 6FT	175x75x16	1545KGS	3500KGS	4240mm	1850mm	5500mm	2311mm	1889mm	939mm	838mm	3



M-TEC Distributor Name:

Contact Number:



Address: Drumconra, Swanlinbar Co.Cavan  
(IRL) 00353 858523737  
(IRL) 00353 04943 20620  
Web: [www.m-tec.ie](http://www.m-tec.ie)



SCAN OUR QR CODE  
to view our full range of products

